

JOINT INVENTORS

"EXPRESS MAIL" mailing label No.
EL564463968US.

Date of Deposit: October 12, 2001

I hereby certify that this paper (or fee) is being deposited with the United States Postal Service "EXPRESS MAIL POST OFFICE TO ADDRESSEE" service under 37 CFR §1.10 on the date indicated above and is addressed to: Commissioner for Patents, Washington, D.C. 20231


Michael Hauman

APPLICATION FOR UNITED STATES LETTERS PATENT

SPECIFICATION

TO ALL WHOM IT MAY CONCERN:

Be it known that we, Kevin Michael Brooks, a citizen of the United States, residing at 36 Gloucester Street, Arlington, MA 02476, and Paula Jean Canavan, a citizen of the United States, residing at 777 N. Michigan Avenue, Apt. 2701, Chicago, IL 60611, and Kenneth Douros, a citizen of the United States, residing at 10 Forest Lane, South Barrington, IL 60010, and Judith Lee Gardner, a citizen of the United States, residing at 7466 Rutherford, Detroit, MI 48228, and Robert Michael Gardner, a citizen of the United States, residing at 829 West Emerald Island Drive, Gilbert, AZ 85233, and Joshua B. Hurwitz, a citizen of the United States, residing at 4020 Newport Lane, Arlington Heights, IL 60004, and Robert H. Leivian, a citizen of the United States, residing at 2702 W. Curry, Chandler, AZ 85224,

and Jens Nagel, a citizen of the United States, residing at 183 Parnassus Ave., #5, San Francisco, CA 94117, and Donald Remboski, a citizen of the United States, residing at 160 Golf Crest Drive, Dearborn, MI 48124, and David John Wheatley, a citizen of the United States, residing at 25318 Barsumian Drive, North Barrington, IL 60010, and Clifford A. Wood, a citizen of the United States, residing at 7227 S. Bonarden, Tempe, AZ 85283, have invented a new and useful "Method and Apparatus for Vehicle Operator Performance Assessment and Improvement," of which the following is a specification.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2

Method and Apparatus for Vehicle Operator Performance Assessment and Improvement

Cross-Reference to Related Applications

5 The present application claims priority to United States Provisional Application Serial No. 60/240,443, filed October 13, 2000 entitled "System for Real-Time Driving Performance Assessment;" United States Provisional Application Serial No. 60/240,444, filed October 13, 2000 entitled "A System for Driver Assistance and Driver Performance Improvement;" United States
10 Provisional Application Serial No. 60/240,493, filed October 13, 2000 entitled "Driver's Cell Phone Assistant;" United States Provisional Application Serial No. 60/240,560, filed October 13, 2000 entitled "Response Selector: A Method of Response Synthesis in Driver Assistance System;" and United States Provisional Application Serial No. 60/240,553, filed October 13, 2000
15 entitled "A System for Driver Performance Improvement," the disclosures of which are hereby incorporated herein by reference.

Field of the Invention

20 The present invention relates generally to the field of vehicle operation, and more particularly, to a method and apparatus for assessing and improving the performance of a vehicle operator.

Background of the Invention

25 The flood of information reaching drivers – telematics, infotainment, collision warning and others – requires a new approach to the operator-vehicle interface. At present, information (such as navigation instructions, cell phone and email messages, traffic warnings, infotainment options, vehicle condition monitoring, etc.) is presented to the vehicle operator asynchronously taking no account of how demanding the driving task might be in a given
30 moment. For example, a "check engine" indicator light might light up among the instruments at the same time a driver is putting a CD into the stereo system, while the navigation system screen displays an upcoming turn and gives a verbal description of that turn, as a cell phone call comes into the car and the driver is engaged in conversation with one or more passengers.

Human beings have a finite ability to perceive the environment, to attend to elements of the environment, to cognitively process the stimuli taken in, to draw appropriate meaning from perceptions, and to act appropriately upon those perceived meanings. Furthermore, there is great variation within the driving population in both native and developed abilities to drive. Thus, vehicle operators are subject to confusion, distraction, and to ignorance, which is exacerbated by the barrage of stimuli they are now subjected to while operating a vehicle. Training, experience, and technology can be used to mitigate confusion, distraction, and ignorance. Unfortunately, in the United States there is little formal or informal training in the skills involved in driving, beyond the period when people first apply for their licenses. Driver training programs have not proven to be particularly effective, nor is training continued through the driving career. In fact, in the United States, in particular, most people think of driving as a right rather than a privilege. Further, studies show that most think of themselves as good drivers and of "the other person" as the one who creates problems. Unless and until a cultural or legal change takes place that encourages drivers to wish to improve their driving skill, it seems that technological solutions designed to minimize confusion, distraction, and ignorance have the best potential for improving the safety of the highway transportation system, which system is likely to become more crowded and, with little or no expansion of the roadway infrastructure likely to occur, therefore, also more dangerous in the future.

To address these and other safety concerns, an integrated safety system based on a state transition model has been proposed. The underlying concept is a "hierarchy of threat" model that steps through a series of states each one representing an assessment of the danger of an impending collision based on information from external object detectors and in-vehicle sensors. The states are "normal driving state," "warning state," "collision avoidable state," "collision unavoidable state," "post-collision state." Sensor and data fusion algorithms combine information from the sensors and determine the degree to which the danger of collision exists. If the system detects the danger of a collision it issues warnings to the driver or, in some situations, takes control of the vehicle and initiates automatic braking, automatic lane change, or other forms of vehicle control. This system represents an attempt

to bring previously unrelated sensor information into an integrated state from which useful inference about the danger of collision may be made and warnings to the driver, or actual control of the vehicle, can be used to avoid completely or mitigate the damage from a collision.

5 There has also been proposed a system that provides extensive monitoring of the vehicle and traffic situation in order to prioritize presentation of information to the driver. The goal of this system is to manage the stream of information to the driver while taking account of the driving task, conditions, and the physical, perceptual and cognitive capacities of the driver. The support provided is designed to improve the driver's focus and to re-focus the
10 attention of a distracted driver as s/he undertakes navigation, maneuvering and control of the vehicle. The overall system architecture incorporates an analyst/planner that accepts inputs from sensors, includes a stored repertoire of driving situations, and records information about the driver. Additionally,
15 the system includes a dialogue controller for managing communication with the driver. The system also monitors the driver and integrates the driver's condition into the decisions made by the warning and control systems.

None of the existing systems undertake the monitoring of a range of sensor data, nor do they provide for evaluation of the driver's cognitive load.
20 Such systems additionally fail to consider the driver's activity in the cockpit that is not directly related to the driving task such as opening and closing windows, tuning the radio, etc. For example, existing systems either do not monitor the driver at all, or monitor the driver relative to static "mode" behavior as opposed to actual dynamic driver performance and/or habits.
25 Thus, these systems do not provide information in synchronization with the driving task, nor do they attempt to minimize distractions and/or to redirect a distracted driver's attention to critical events.

Additionally, previous systems that have attempted to assess driver performance have been limited to lane-following capability, that is, evaluating
30 how well the driver maintains the position of the vehicle relative to the edges of the lane in order to generate a parameter representing the driver's lane-following ability. The parameter is periodically determined, and if it falls below an established level, a warning, such as a buzzer or visual indication, is presented to the driver. This system is limited in that it only provides lane-

following evaluation and does not account for deliberate lane departures such as to avoid a hazard, is not integrated to receive a spectrum of sensor input, and does not include driver condition and driver activity data. Though such a measure will identify degraded vehicle control, it is questionable whether it will
5 identify cognitive or mental distraction.

Furthermore, none of these systems provide feedback to the driver relative to their overall performance, nor do they provide feedback relative to improving driver performance.

Thus, there is a need to provide information to the vehicle operator in
10 synchronization with the driving task so as to improve operator focus, minimize distractions and ensure the operator's ability to assimilate and use the information. There is a further need to re-direct a distracted operator's attention from non-mission critical activities to prioritized information and/or tasks necessary to maintain safe operation of the vehicle. There is an
15 additional need to provide feedback to the vehicle operator relating to performance and to provide additional feedback designed to assist the operator in improving performance.

Brief Description of the Drawings

The invention is described in terms of several preferred embodiments with reference to the attached figures wherein like reference numerals refer to like elements throughout.

FIG. 1 is a block diagram of an operator performance assessment
25 system in accordance with a preferred embodiment of the invention.

FIG. 2 is block diagram illustrating an interface of the driver with the vehicle in accordance with a preferred embodiment of the invention.

FIG. 3 is a block diagram illustration of a wireless communication device according to a preferred embodiment of the invention.

FIG. 4 is a flow chart illustrating the steps of a method of assessing vehicle operator performance in accordance with a preferred embodiment of the invention.

FIG. 5 is a flow chart illustrating the steps of a method of improving vehicle operator performance in accordance with a preferred embodiment of the invention.

5 FIG. 6 is a flow chart illustrating the steps of a method of synthesizing a response to vehicle operating conditions in accordance with a preferred embodiment of the invention.

FIG. 7 is a flow chart illustrating the steps of a method of providing feedback to a vehicle operator in accordance with a preferred embodiment of the invention.

10 FIG. 8 is a flow chart illustrating the steps of a method of configuring a service state of a wireless communication device in accordance with a preferred embodiment of the invention.

Detailed Description of the Preferred Embodiments

15 A system is adapted to assess information incoming to a vehicle operator, to prioritize the information based upon a number of conditions relating to the vehicle operation, the operating environment, the activity of the operator and the physical condition of the operator, and to provide to the operator the most pertinent information for the given set of conditions. As
20 used throughout this specification, the terms vehicle operator and driver are used interchangeably and each are used to refer to the person operating the vehicle in the manner in which the vehicle is intended to be operated.

In another embodiment of the invention, the system monitors various data sources, including the vehicle operation, the operating environment, the
25 activity of the operator and the condition of the operator, and provides an assessment of the operator's performance. In doing so, the system may additionally identify the particular vehicle operator such that the assessment may be made relative to operator preferences, past driving performance and habits.

30 The system is further adaptable to assist the operator in improving performance. The system monitors various data sources, including the vehicle operation, the operating environment, the activity and condition of the operator, over a period of operation and records the operator's performance. The performance may be compared with accepted good practices, and a

report may be provided to the operator indicating how the operator's performance compares with the accepted good practices and/or with the operator's previous driving performance and/or habitual behavior. The system may record operator performance over a number of periods of operation, and provide comparisons of operator performance from period to period.

The system is further adaptable to act in response to an assessment of the vehicle operation, the operating environment, the activity of the operator and the condition of the operator to avoid or mitigate a problem situation associated with operation of the vehicle.

Referring then to FIG. 1, a system 100 includes a sensor fusion module 102, a response selector module 104 and an action generator 106. The sensor fusion module 102, response selector module 104 and action generator 106 are illustrated in FIG. 1 as separate elements for purposes of clarity and discussion. It will be appreciated these modules may be an integrated into single module. Moreover, it will be appreciated that each of these modules, or an integrated module, may include a suitable processing device, such as a microprocessor, digital signal processor, etc., one or more memory devices including suitably configured data structures, and interfaces to couple the system 100 to various vehicle sensors and to interface with a driver 108.

The sensor fusion module 102 receives data from numerous sources within and surrounding the vehicle. As illustrated in FIG. 1, the sensor fusion module 102 receives vehicle operating data 112, vehicle environment data 114, driver condition data 116 and driver activity data 118.

The vehicle operating data 112 encompasses data produced by the various vehicle sensors. Vehicle condition monitoring sensors are pervasive in an automobile. These sensors monitor numerous parameters such as engine operating parameters, vehicle speed, transmission and wheel speed, vehicle acceleration in three axes, chassis function, emission control function, etc. These sensors may also provide data related to vehicle diagnostics.

Vehicle environment data 114 encompasses data related to the environment in which the vehicle is operating, e.g., the road conditions, traffic conditions, weather, etc. The vehicle environment data 114 may be provided

by sensors that also provide vehicle-operating data 112. For example, road surface and traction estimates may be provided by anti-lock braking, traction control and chassis control system sensors. Vehicle location may be provided by an on-board navigation system utilizing global positioning system (GPS)

5 technology, or location information may be provided by a wireless communication device (e.g., a cellular telephone) and associated wireless communication network. Radar, laser, ultra-sonic and video systems can provide a map of objects near the vehicle and their motion relative to the vehicle. Weather and time of day may also be monitored directly or derived
10 from reported sources.

Driver condition data 116 and driver activity data 118 may be provided by various cockpit monitoring systems. Seat sensors and/or infrared sensors may sense the number and locations of passengers in the vehicle. Floor and steering wheel sensors may indicate the position of the driver's feet and
15 hands. Video or imaging sensors may monitor head, body, hand and feet movements of the driver, and the operative states and driver usage of infotainment and telematics systems may also be monitored.

As will be appreciated, numerous sources of data exist within and about the vehicle environment, which may be utilized by the system 100.

20 Several data types have been described above, others will be described in connection with the operation of the system 100, and still others not specifically referred to herein may be used without departing from the scope and spirit of the invention. It will be appreciated that as new technologies introduce new types and sources of data and new types and sources of
25 information into the vehicle, the system 100 may be adapted to utilize these additional sources of data to manage how the existing and new sources of information are presented to the driver.

In other words, the system 100 will monitor anything of a technical nature that the driver might be touching or using in the cockpit of the vehicle
30 so that the system 100 knows as much as possible about what the driver is doing at any given moment. Further, the use of video or imaging technology, seat sensors and microphones in the cockpit allows the system 100 to determine the location and position of the driver, the noise level, and the presence of passengers and other potential sources of distractions. The

radar, laser, video and infra-red sensors deployed around the perimeter of the vehicle monitor traffic and weather conditions, obstacles, lane markings, etc. The drivers' present condition and driving performance is inferred from direct measures, such as video, and from comparison of current performance with
5 past performance and known good performance practices.

In addition to obtaining data from a variety of sources, the system 100 interfaces with the vehicle operator/driver 108. While operating the vehicle, the driver 108 is engaged in a number of different actions, such as, but
10 certainly without limitation, applying the accelerator or brakes, turning the steering wheel, checking blind spots, adjusting the radio, receiving a cellular telephone call, obtaining navigation information, carrying on a conversation with a passenger, quieting the kids in the rear seat, etc. Each of the driver's actions, which for discussion purposes are illustrated as box 110 in FIG. 1, are fed back to the sensor fusion module 102 via the sensors. Additionally, as
15 will be described in greater detail, the system 100 presents information, actions and tasks to the driver 108 via the action generator 106. This "closed" loop operation may continue for a given situation until the situation is resolved. In one very limited example to illustrate the concept, a change oil soon indication may be generated by the powertrain management system on
20 the vehicle. Previously, this indication would cause a "service engine" or "change engine oil" light to be illuminated on the vehicle instrument panel as soon as the powertrain management system generated the indication. The light suddenly appearing among the instruments may temporarily distract the driver. If at the time the light is illuminated the driver is negotiating traffic or
25 otherwise in a situation requiring full attention to the driving task, the distraction may present a hazard. In accordance with the preferred embodiments of the invention, the non-critical data relating to changing the engine oil may be saved until conditions allow for the information to be presented to the driver at a time less likely to create a hazard situation. In
30 that regard, the system 100 operates continuously taking in data and re-timing its presentation to the driver. Moreover, the system 100 continuously evaluates the information to be provided to the driver to determine when and how to best provide it to the driver. This operation of the system 100 may be illustrated by an additional example. A low fuel alert may initially be a non-

critical piece of information relative to current driving conditions but may become a critical piece of information if the driver is about to pass the last gas station, as system 100 is informed by the on-board navigation system, within the remaining range of the vehicle.

5 Referring to FIG. 2, a number of interfaces exists between the driver 108 and the vehicle and hence to the system 100. Various interfaces are discussed below, and may include driver identification 200, instrumentation and alerts 202, vehicle controls 204, driver condition sensors 206 and driver activity sensors 208.

10 Due to the wide variation in human skill-levels, physical size, and personal preferences and tastes, there are many situations where it would be useful for the system 100 to "recognize" who is attempting to enter and/or drive the vehicle. In that regard, the driver identification interface 200 may be configured as a personal portable user interface (PPUI). A PPUI may exist in
15 many forms, but in essence captures preference, performance and habit data associated with a particular driver. The PPUI may be encoded on a smart card or embedded in the vehicle to be activated by a fingerprint reader, voice recognition system, optical recognition system or other such means.

In various embodiments, the PPUI may function as a security system
20 granting or limiting access to the vehicle or the vehicle's ignition system, and bars access to unauthorized persons or disables the vehicle when an unauthorized person attempts to drive the vehicle. The PPUI may also capture driver preferences as it relates to a number of active safety features. Through the PPUI (driver identification interface 200), the system 100 is
25 informed of the driver preferences. For example, the driver may select what types, under what conditions and how alerts are communicated. For example, a driver may prefer to receive an alert each time the system 100 detects too short a headway relative to a speed of travel. For another driver, a high level of alert might be perceived as a nuisance resulting in the alerts
30 being ignored and/or the system 100 being disabled. Similarly, a driver may wish to have immediate access to all in-coming cell phone calls, while another driver may wish to have only certain calls put through. The PPUI as part of the driver identification interface 200 permits each operator of the vehicle to establish choices ahead of time.

The PPUI may also function in a driver performance improvement and/or driving restriction enforcement tool. The PPUI may be used to monitor driving performance and report to a traffic enforcement authority. This would allow a habitual traffic offender to retain driving privileges in a court-monitored fashion. Driving performance may be recorded for subsequent review, and a method of improving driver performance is described herein. Additionally, the PPUI may be used to implement controls on the usage of the vehicle. For example, a parent may restrict the distances and locations a vehicle may be taken or the hours of the day the vehicle may be operated by a newly licensed driver. An employer may monitor the driving habits of its fleet drivers.

In operation, the system 100 is programmed to recognize, based on the received data, "situations" and "conditions" that might arise during operation of a vehicle. The system 100 may be configured to actuate, relative to priorities for the presentation of information and the thresholds for the levels of alerts, warnings and alarms. The driver identification interface 200 including the PPUI provides the driver with choices relating to the priorities, thresholds and interfaces, and operates to synchronize the choices with the appropriate driver.

The instrumentation and alerts interface 202 is used by the system 100 to inform, advise and in the appropriate situations alert and warn the driver 108. The instrumentation and alerts interface 202 may include visual, audio, haptic or other suitable indicators. Visual indicators may include gages, lighted indicators, graphic and alphanumeric displays. These visual indicators may be located centrally within the instrument panel of the vehicle, distributed about the vehicle, configured in a heads-up-display, integrated with rearview and side view mirrors, or otherwise arranged to advantageously convey the information to the driver 108. The audio indicators may be buzzers or alarms, voice or other audible alerts. The haptic alerts may include using the chassis control system to provide simulated rumble stripes, pedal or steering wheel feedback pressure, seat movements and the like. The actuation of any one or more of the indicators or alerts is controlled by the system 100 in order to synchronize the timing of information as it is provided to the driver.

The vehicle controls interface 204 includes the primary controls used by the driver to operate the vehicle. These controls include the steering

wheel, accelerator pedal, brake pedal, clutch (if equipped), gear selector, etc. These controls may include suitable position and/or actuation sensors and may further include at least in the case of the accelerator pedal, brake pedal and steering wheel rate of input and/or force of input sensors. Additional
5 sensor data may include yaw rate of the vehicle, wheel speed indicating vehicle speed and traction, tire pressure, windshield wiper activation and speed, front and/or rear window defogger activation, audio system volume control, and seat belt usage sensors.

The driver condition interface 206 utilizes various sensors to infer driver
10 condition. For example, an alert driver continuously makes steering corrections to maintain the vehicle in its lane. By monitoring steering wheel sensors, the system 100 gathers data about the frequency and amplitude of the corrections to infer if the driver has become impaired. Speed sensors may also be queried in a similar manner. Video or other imaging sensors
15 provide direct measurement of the drivers' condition via monitoring of such criteria as driver blink rate and gaze.

The driver activity interface 208 utilizes various sensors and imaging technology to determine the activity of the driver. That is, to determine if the driver, in addition to operating the vehicle, is adjusting the radio or heating,
20 ventilation and air conditioning (HVAC) controls, initiating or receiving a wireless communication, receiving navigation information, and the like. These sensors may include seat pressure sensors to determine the number of passengers in the vehicle, and the activities of the passengers and video or other imaging technology to observe the driver's movements.

Referring again to FIG. 1, and as previously noted, the sensor fusion
25 module 102 receives all of the various sensor inputs, including those measuring vehicle condition, driver condition, driver activity and operating environment (e.g., weather, road and traffic conditions), and produces a set of conditions or master condition list. The conditions represent the current
30 discrete state of each thing the sensor fusion module 102 is monitoring. For example, the speed condition may be in one of the following states at any point in time: "stopped," "slow," "normal," "fast," and "speeding." The states are determined based upon learned thresholds between the states and based on history and known good practices. The sensor fusion module 102, given

the master condition list, evaluates the current drivers tasks and activities, such as tuning the radio, listening to e-mail or other potentially distracting tasks, to produce an estimated driver cognitive load. The cognitive load of each static task may be determined externally by controlled experiments with a set of test subjects (e.g., tuning the radio might use 15.4 percent of a driver's attention). The total cognitive load is the weighted sum of each of the individual tasks. The weighting may be fixed or may change, for example exponentially, given the number of concurrent tasks.

The master condition list and the estimated driver cognitive load is then provided to the response selector module 104. The response selector module looks at the conditions, current driving situation and cognitive load to determine if a problem exists and further assesses the severity of the problem. The response selector module 104 further takes into account driver preferences, to choose a response appropriate to the driver's present task and prioritizes the presentation of alerts, warnings and other information to the driver. The response selector module 104 may incorporate a reflex agent that uses decision tree or look-up tables to match states with desired actions. Alternatively, an adaptive, i.e., learning, goal-seeking agent may be used. Thus, the response selector module 104 synthesizes and summarizes sensor data creating a correct response to any given condition change.

In one possible implementation, the response selector module 104 may include programmer-entered parameters which are used to determine if a condition change a) creates a problem, b) solves a problem, c) escalates a problem, d) initiates a driver task, e) initiates an agent task, f) completes a driver or agent task, g) changes the situation or h) is innocuous. The estimated cognitive load may be used to determine an urgency of an identified problem or whether a response to the problem should be initiated by the driver or by an agent. For example, an incoming cellular phone call may be directed to the driver if the driver's estimated cognitive load is below a threshold value for receiving cellular telephone calls. If the driver's cognitive load exceeds the threshold value for receiving cellular telephone calls, then the cellular telephone call may be forwarded to voice mail (i.e., an agent device).

The response selector 104 activates the action generator 106 in order to effect the selected response. The action generator 106 may be a library of actions that the system is equipped to perform, such as in the above example, forwarding a cellular telephone call to voice mail. The library may include
5 actions along with instructions, which may be software instructions for causing the associated processor to act, i.e., to actuate all potential alerts and warnings that can potentially be provided to the driver.

Fusion of sensor data, including data relating to the driver's condition and activity allows the system 100 to operate to assess driver performance.

10 As noted, the system 100 is operable to identify a driver through the driver identification interface 200. During operation of the vehicle by the driver, the system 100 monitors several aspects of driver performance to arrive at a driver performance assessment value.

In one embodiment, the system 100 may monitor the driver's lane
15 following ability. Information on lane-exceedence is recorded relative to the use of turn signals and to subsequent movement of the vehicle to determine whether the lane change was intentional or unintentional. Additionally, the system 100 may monitor gaze direction, blink rates, glance frequency and duration to determine the driver's visual scanning behavior including the use
20 of mirrors and "head checks" when changing lanes. The information may be used in comparison to known "good habits" to assess performance, and at the same time, may be used to develop a metric reflecting the driver's normal patterns, which can be used as a baseline to compare changes in driving behavior as well as to monitor degradation or improvement in driving skill.

25 Additional information that may be taken into consideration to assess driver performance includes application of the accelerator and brakes. The driver's use of the accelerator and brakes is recorded and given a numeric value. Again, using comparison algorithms to known "good habits" and to past performance an assessment of how smoothly the driver is braking and/or
30 accelerating may be made as well as the number and severity of panic stops. Accelerator and brake pedal data may also be used in conjunction with metrics of headway maintenance, as monitored by the system 100. Doing so allows the system 100 to determine whether the driver is waiting too long to brake relative to obstacles in the forward path of the vehicle and even to

determine whether the driver is prone to unsafe headway when vehicle speed control devices are used.

In addition to assessing driver performance, the system 100 may be adapted to assist in the improvement of driver performance. Communication of the driver assessment to the driver encourages the driver to perform better. The system 100 may also provide specific advice relating to improving driver performance. For example, the monitoring of driver performance may extend temporally (recording and comparing the driver's performance over time) and spatially (considering performance variation on familiar, frequently-traveled routes) to include all of the times that a particular driver has driven the equipped vehicle. The driver assessment, i.e., driver performance, including alerts, warnings and suggestions for improved performance, is then provided to the instrumentation/alerts module 202 for communication to the driver. A library of pre-recorded messages to the driver may be accessed by the system 100 and appropriate messages constituting reports and suggestions, are chosen. For example, the system 100 may have detected that the driver has not been doing head-checks before changing lanes, and may draw the driver's attention to that fact and state the reason that merely glancing at the mirror is not a good substitute for a head-check. Additional messages may include reminders about improving fuel economy or specifically identify an area of driving performance that deteriorated over the course of trip.

Communication of performance improvement information may be made real time; however, to avoid creating further distractions for the driver, the information may be stored and communicated to the driver following a driving activity. Triggering events and/or thresholds may be used to actuate delivery of the performance improvement messages. Alternatively, the driver may optionally select to activate the interface. The stored performance information may also be downloaded from the vehicle and used as part of a classroom or simulator-based continuing training program, a driver skills assessment program or a traffic enforcement program.

To encourage usage of the system 100 to improve driving performance, the feedback may be configured to appeal to particular categories of drivers. For example, for younger drivers, pre-recorded messages using the voices and likenesses of motor racing personalities may

be used to convey the information, while for other drivers pre-recorded message using well known and trusted personalities may be used. Alternatively, the system 100 may generate messages using speech synthesis.

5 One particularly example of potential driver distraction relates to usage of cellular telephones. As described, the system 100 synthesizes and prioritizes all incoming information, including cellular telephone calls. For example, the system 100 may provide two potential cut-offs of cellular telephone calls to a driver without completely prohibiting calls. In the first
10 instance, the caller is informed, by a pre-recorded message, that the call is being completed to a person presently driving a vehicle. The caller is then given the option of having the call sent directly to voice mail or putting the call through to the driver. Before the call is completed to the driver, the system 100 evaluates the situation, conditions and the driver's cognitive load to
15 determine if the response, sending the call through, is appropriate. If the system 100 determines that the potential for driver distraction is beyond certain desired limits, e.g., the required driver cognitive load will exceed a threshold, the incoming call may be held and/or automatically transferred to voice mail with an appropriate pre-recorded message.

20 The system 100 may be configured to substantially limit the number of calls coming in to the driver. Many times a caller does not know the person they are calling is driving, and if they did, may not have called. As described above, the system 100 provides a mechanism for informing the caller that they are calling a driver and provides the option to divert the call to voice mail.
25 Alternatively, the system 100 may be configured to give the driver the option of accepting calls transparent to the caller. In such an arrangement the incoming call is identified to the driver via a hands-free voice interface. The driver may then accept the call, refer the call to voice mail, refer the call to a forwarding number or to terminate the call, all of which may be accomplished
30 without the caller's knowledge. Alternatively, the call completion may be delayed shortly, with an appropriate message being provided to the caller. The system 100 may then complete the call after the short delay once it is determined that the driver's cognitive load is at an acceptable level.

The system 100 may also be adapted to take "corrective" action in the event that an on-going call is coupled with a degradation of driving performance. If after accepting a cellular telephone call the system 100 determines that the driver's cognitive load has increased beyond a threshold level and/or if there is a degradation in driving performance below a threshold level, the system 100 may automatically suspend the cellular telephone call. In such instance, a message is provided that informs the caller they are being temporarily placed on hold. The system 100 may also offer the caller an option to leave a voice mail message. Additionally, so that the driver is aware of the call interruption, an appropriate message is provided to the driver indicating that the call has been placed on hold. The driver likewise may refer the caller to voice mail.

As with other aspects of the operation of the system 100, the driver's preferences as to cellular telephone usage is provided to the system 100 via the driver identification interface 200. The system 100 may also operate with other wireless communication devices including personal digital assistants (PDAs) and pagers for receiving email and text and data messages.

To take advantage of the ability of the system 100 to prioritize incoming cellular telephone calls with other information presented to the driver requires the cellular telephone be communicatively coupled to the system 100 and controllable by the system 100. A stand-alone cellular telephone, that may not be adaptable to the system 100, may be adapted to operate in a context aware manner.

FIG. 3 illustrates a hand-held cellular telephone 300 including a processor 302, a memory 304, a sensor fusion module 306 and a plurality of sensors, one of which is illustrated as sensor 308. While shown as separate elements, it will be appreciated that these elements of the cellular telephone 300 can be integrated into a single unit or module. Alternatively, a sensor fusion module including appropriate processing capability may be provided as an add-on device to existing cellular telephones. The sensor(s) 308 may take in such data as ambient lighting, temperature, motion and speed, date and time and location. Of course, where the cellular telephone 300 is operated in a wireless communication network environment information such as location, speed, date and time may be provide by the network. However, the sensor

308 may be a GPS device capable of determining location, speed, time and day using the GPS satellite system.

The sensor fusion module 306 receives the data from the various sensors and creates a master condition list that is communicated to the processor 302 controlling the operation of the cellular telephone. The processor 302 operates in accordance with a control program stored in the memory 304 and using the master condition list to provide context aware operation of the cellular telephone 300. Context aware operation of the cellular telephone 300 can be illustrated by the following examples.

In one example of context aware operation, the cellular telephone is determined to be moving at a speed of 60 kilometers per hour (kph). This condition is reported by the sensor fusion module 306 as part of the master conditions list to the processor 302. The processor 302 infers from this speed condition that the cellular telephone is with a driver of a vehicle, and thus enters a service state where incoming calls are screened. One form of screen is as described above, wherein the caller is first advised that they are calling a driver and offered the option of leaving a voice message.

In another example of context aware operation, the cellular telephone is determined to be at approximately human body temperature. This condition is reported by the sensor fusion module 306 as part of the master conditions to the processor 302. The processor 302 operates in accordance with the control program and using the master condition list determines the cellular telephone 300 is likely located close to the user's body. Instead of operating in a ringing service state, the cellular telephone 300 is caused to operate in a vibrate service state to announce an incoming call.

The following Table I set forth various sensor mechanism, context estimates and operation service states.

Sensor Mechanism	Context Estimates	Service State
Network Infrastructure <ul style="list-style-type: none">• Capability of determining location & velocity through triangulation or Doppler shift analysis• Capability of	<ul style="list-style-type: none">• In an airplane• In a moving vehicle• Near or on a highway• Not in a moving vehicle• Carried by	<ul style="list-style-type: none">• No use in an airplane (to comply with FAA regulations—subject override)• Limit when driving<ul style="list-style-type: none">○ In intersections○ In cities○ On highways

<p>recording and comparing temporally and spatially the location and velocity (above) to enable tracking</p> <ul style="list-style-type: none"> Map matching database determines location relative to infrastructure, buildings, points of interest Clock/timer 	<p>someone walking or running</p> <ul style="list-style-type: none"> Time of day Day of week 	<ul style="list-style-type: none"> Above certain speeds Limit by location <ul style="list-style-type: none"> Theaters, concerts, houses of worship, etc. Limit by time of day, day of week <ul style="list-style-type: none"> Hours of rest, meals, meetings, family time, etc. Workday rules vs. Weekend rules Specify callers
<p>Standalone Handset/ Add-on Module</p> <ul style="list-style-type: none"> Location Velocity Track Light (Photometer) Temperature (Thermometer) Acceleration (vibration and orientation) (Accelerometer) Background noise (Microphone) Chemical sensor Smoke sensor Clock Altimeter 	<p>All of the above plus:</p> <ul style="list-style-type: none"> How close to normal human body temperature? How likely in a purse or briefcase? (dark and sound muffled) In a pocket? (low light level, not body temperature) On a belt? Determine level of ambient noise Determine presence of chemical/smoke 	<ul style="list-style-type: none"> If close, vibrate instead of ringing In no light and sound muffled, ring louder If in pocket but not next to body, ring instead of vibrating Vibrate instead of ringing Modulate volume of ringer and speaker relative to ambient noise level Ringling alarm

<p>In-vehicle</p> <ul style="list-style-type: none"> • All vehicle control and accessory sensors • All externally deployed sensors determining information about the driving environment • All actuators and cockpit sensors to determine what the driver is doing • All sensors deployed to determine the driver's condition 	<p>All of the above, plus:</p> <ol style="list-style-type: none"> 1. Gaze tracker knows that driver is looking elsewhere than through the windshield or at the mirrors 2. Navigation system knows that a complicated maneuver or a dangerous curve is coming up. 3. Vehicle sensors indicates potentially dangerous degradation of the vehicle 4. Driver already engaged with a different wireless device 5. Potentially dangerous situation arises while driver already engaged in wireless communication 	<ol style="list-style-type: none"> 1. If driver's glance does not return to windshield or mirrors within TBD seconds, communication diverted to voice mail. 2. Message delayed or diverted to voice mail. 3. Message delayed or diverted to voice mail. 4. Message taken 5. Call interrupted, caller offered voice mail or hold, person called informed that call is being dropped and will be resumed when safe to do so.
--	---	---

Table I Context Aware Wireless Device Service States

In accordance with the preferred embodiments of the invention, methods of: assessing vehicle operator performance, informing the vehicle operator to improve the operator's performance, response synthesis in a driver assistant system, improving driver performance through performance feedback and context aware device operation are described in connection with FIGs. 4-8.

Referring to FIG. 4, a method 400 of assessing vehicle operator performance begins at step 402 with receiving vehicle operating data from the vehicle relating to the vehicle operating condition. Step 402 involves receiving at the sensor fusion module 102 data from the various sensors, systems and

device in the vehicle data relating operation of the vehicle. This data may include vehicle speed and vehicle acceleration, throttle application, brake application, steering wheel input, throttle position, rate of change of throttle position, additional available throttle input and throttle applicator pressure,

- 5 brake position, rate of change of brake position, additional available brake input and brake applicator pressure, steering wheel position, rate of change of the steering wheel, operator pressure applied to the steering wheel, additional available steering input and other operating parameter of the vehicle such as oil temp, oil pressure, coolant temp, tire pressure, brake fluid temp, brake fluid
10 pressure, transmission temp., misfire, windshield wiper activation, front/rear defogger application, diagnostic systems, etc.

At step 404, an interior portion of the vehicle is monitored to provide data to the sensor fusion module 102 relating to activities of the driver.

- Monitored activities may include monitoring the usage of vehicle system
15 controls by the driver, such as driving controls, telematics systems, infotainment systems, occupant comfort controls including HVAC, seat position, steering wheel position, pedal position, window position, sun visors, sun/moon roof and window shades and communication controls. Monitoring activities may also include monitoring activities of the vehicle passengers.

20 At step 406, the vehicle environment external to the vehicle is monitored to provide data to the sensor fusion module 102 relating to the operating environment of the vehicle. The operating environment data may include road condition, lane following, headway data, traffic control data and traffic condition data.

- 25 At step 408, the vehicle operator is monitored to provided data to the fusion module 102 relating to the condition of the driver. The driver physical condition may include fatigue or intoxication or a psychological condition of the driver. Additionally, a distraction level of the driver may be monitored.

- At step 410 the driver performance is assessed. The driver's
30 performance may be assessed by inferring driver performance from the vehicle operating data, the operator activity data, the environment data and the operator condition data. Such an inference may be drawn using inference engine or a rules-based decision engine. Alternatively, fuzzy logic or adaptive, goal-seeking may be used.

Referring to FIG. 5, a method 500 of informing a driver to improve driver performance begins at step 502 with receiving vehicle operating data from the vehicle relating to the vehicle operating condition. Step 502 involves receiving at the sensor fusion module 102 data from the various sensors, systems and device in the vehicle data relating operation of the vehicle. This data may include vehicle speed and vehicle acceleration, throttle application, brake application, steering wheel input, throttle position, rate of change of throttle position, additional available throttle input and throttle applicator pressure, brake position, rate of change of brake position, additional available brake input and brake applicator pressure, steering wheel position, rate of change of the steering wheel, operator pressure applied to the steering wheel, additional available steering input and other operating parameter of the vehicle such as oil temp, oil pressure, coolant temp, tire pressure, brake fluid temp, brake fluid pressure, transmission temp., misfire, windshield wiper activation, front/rear defogger application, diagnostic systems, etc.

At step 504, an interior portion of the vehicle is monitored to provide data to the sensor fusion module 102 relating to activities of the driver. Monitored activities may include monitoring the usage of vehicle system controls by the driver, such as driving controls, telematics systems, infotainment systems, occupant comfort controls including HVAC, seat position, steering wheel position, pedal position, window position, sun visors, sun/moon roof and window shades and communication controls. Monitoring activities may also include monitoring activities of the vehicle passengers.

At step 506, the vehicle environment external to the vehicle is monitored to provide data to the sensor fusion module 102 relating to the operating environment of the vehicle. The operating environment data may include road condition, lane following, headway data, traffic control data and traffic condition data.

At step 508, the vehicle operator is monitored to provided data to the fusion module 102 relating to the condition of the driver. The driver physical condition may include fatigue or intoxication or a psychological condition of the driver. Additionally, a distraction level of the driver may be monitored.

At step 510, the driver's cognitive load is estimated. The driver's cognitive load may take into account driver preferences, past performance

and habits. Then, at step 512, vehicle information is prioritized based upon the driver's cognitive load for communication to the driver.

Referring to FIG. 6, a method 600 of synthesizing a response to an operating situation of a vehicle begins at step 602 with the generation of a master condition list. The master condition list is generated by the sensor fusion module 102 and is a fusion of the various sensor data available within the vehicle. The sensor data may be any available data within the vehicle including: vehicle operating data, driver activity data, environment data, driver condition data, driver preference data, driver action feedback data.

From the master condition list, at step 604, an operating situation is determined. The operating condition may be: the existence of a problem condition, the existence of a problem correction, the existence of a problem escalation, the existence of an operator task requirement, the existence of an agent task requirement, the existence of a completion of an operator task, the existence of a completion of an agent task. Additionally, at step 606, an operator cognitive load is determined.

At step 608, a response to the operating situation is determined based on the operator cognitive load. The response may be synchronizing an information flow to the driver, generating an alert to the driver, providing an alert including audio alerts, a visual alerts and haptic alerts, suspending or terminating operation of selected services within the vehicle.

Referring to FIG. 7, a method 700 of improving driver performance through performance feedback begins at step 702 with receiving vehicle operating data from the vehicle relating to the vehicle operating condition. Step 702 involves receiving at the sensor fusion module 102 data from the various sensors, systems and devices in the vehicle and data relating operation of the vehicle. This data may include vehicle speed and vehicle acceleration, throttle application, brake application, steering wheel input, throttle position, rate of change of throttle position, additional available throttle input and throttle applicator pressure, brake position, rate of change of brake position, additional available brake input and brake applicator pressure, steering wheel position, rate of change of the steering wheel, operator pressure applied to the steering wheel, additional available steering input and other operating parameter of the vehicle such as oil temp, oil pressure,

coolant temp, tire pressure, brake fluid temp, brake fluid pressure, transmission temp., misfire, windshield wiper activation, front/rear defogger application, diagnostic systems, etc.

At step 704, an interior portion of the vehicle is monitored to provide

- 5 data to the sensor fusion module 102 relating to activities of the driver.

Monitored activities may include monitoring the usage of vehicle system controls by the driver, such as driving controls, telematics systems, infotainment systems, occupant comfort controls including HVAC, seat position, steering wheel position, pedal position, window position, sun visors, 10 sun/moon roof and window shades and communication controls. Monitoring activities may also include monitoring activities of the vehicle passengers.

At step 706, the vehicle environment external to the vehicle is monitored to provide data to the sensor fusion module 102 relating to the operating environment of the vehicle. The operating environment data may 15 include road condition, lane following, headway data, traffic control data and traffic condition data.

At step 708, the vehicle operator is monitored to provided data to the fusion module 102 relating to the condition of the driver. The driver's physical condition may include fatigue or intoxication or a psychological condition of 20 the driver. Additionally, a distraction level of the driver may be monitored.

At step 710, the driver's performance assessment is determined and is recorded so that at step 712, the driver's performance assessment may be reported to the driver. Step 712 includes reporting the driver performance assessment upon conclusion of vehicle operation or reporting the operator 25 performance assessment during operation of the vehicle. Moreover, the driver's performance assessment may be recorded for a first period of vehicle operation and for a second period of vehicle operation and include a comparison of the two performances.

The method may further include the step of receiving driver preference 30 data and recording the driver performance assessment based on the driver preference data. Additionally, the driver performance assessment may include a score for each of a plurality of aspects of vehicle operation. Reporting the driver performance assessment may be by visual indication, audio indication or haptic indication.

Referring to FIG. 8, a method 800 for configuring a service state of a wireless communication device begins at step 802 with receiving a set of device operating parameters defining a preferred service state of the wireless communication device for a device operator. At step 804, context data is received from at least one context data source. The device operating parameters includes at least a context parameter. The context parameter and the context data may each relate to: a speed of the wireless communication device, a location of the wireless communication device, time, an activity of the device operator, a cognitive load of the device operator, an operation of a vehicle including vehicle operating data and environment data, ambient lighting, altitude and ambient sound. The data received may be a fusion of data from a variety of sources, such as from within the vehicle where the wireless communication device is communicatively coupled to the vehicle. The device operating parameters may be provided via a personal portable user interface, such as vehicle identification interface 200.

At step 806, a service state of the wireless communication device is set. The service state may be: call forwarding, call forwarding to voice mail, voice activated, ringing mode, call completion delay and calling party identification, etc.

The wireless communication device may be a cellular telephone, a pager, a personal digital assistant or other computing device including personal computers and web browsers.

The invention has been described in terms of several preferred embodiments, and particularly to systems and methods for synthesizing and summarizing information and the presentation of information to a driver. Modifications and alternative embodiments of the invention will be apparent to those skilled in the art in view of the foregoing description. This description is to be construed as illustrative only, and is for the purpose of teaching those skilled in the art the best mode of carrying out the invention. The details of the structure and method may be varied substantially without departing from the spirit of the invention, and the exclusive use of all modifications, which come within the scope of the appended claims is reserved.